

Regular Adhesive Technical Data Specifications

Face-stock:

A glossy white top coated direct thermal paper with protective top coating. This product features a bright white facestock that is top coated for optimum environmental resistance. It is suitable for flexography and thermal printing system and has an excellent barcode print performance.

Base Weight:	70±3 g/m ²	GB/T451.2
Caliper:	72±3 um	GB/T451.3

Adhesive:

Permanent Rubber Base Hot Melt Adhesive

Liner:

A white super calendered glassine with good internal strength and luminousness. It has characters of high-temperature, moisture and oil resistance. It is suitable for high-speed auto labeling liner, printing & die-cutting design. It has excellent performance in Die cutting processing.

Base Weight	58±2 g/m ²	GB/T451.2
Caliper	50±3 um	GB/T451.3

Performance Data:

Loop Tack	15-20 N	GB/T 31125-2014
180°Peel Strength	7-8 N/CM	GB/T 2792
Min Apply Temperature	0℃	
Service Temperature	-55℃-65℃	

Adhesive Performance

A good performance and wide temperature tolerance permanent hot melt adhesive. The adhesive features excellent tack and adhesion on a wide variety of clean substrates like paper, metal, glass, PP/PE/PET, etc. under room temperature.

Application and use:

The face paper has excellent resistance to scratch, moisture and chemicals. It is suitable for flexography and thermal printing system and has an excellent barcode print performance. It is not suggested to print color on the print aimed area. It is not suggested to apply under cold environment.

Shelf life: one year at 23±2℃, RH 50%

Creation Date: Aug. 10, 2022

Version: C/01